

## Compact and Youth Compact Rules

2023 Delaware County Fair

September 23rd at 5:00 P.M.

Gates open at Noon for Inspection - \$30.00 entry fee

### General Information

\*\*\*\*\* Traffic Is ALWAYS an issue. Plan accordingly, There WILL BE A \$50.00 late fee for registration and inspection to any person not registered 1 hour before showtime \*\*\*\*\*

1. The Driver must be registered and vehicle must be inspected 1 hour prior to start time of show or a \$50 late fee will be imposed before your vehicle will be inspected. There will be NO EXCEPTIONS! Inspection will close 15 minutes prior to the drivers meeting and the start of the derby, it is the responsibility of the driver to be there on time. No Exceptions!

During and after the Derby, there will be very limited help available to load ran cars. They will be removed from the track after each heat and if the car is unable to move it will be put back in the staging area. You can come and load your car on your own if capable, and in a safe and secure way, again limited loading help may be available but only in a safe and secure manner, or the following day a loader will be available inside a couple hour window in the morning to help load the remaining cars if you would prefer to return after it. This is an ABSOLUTE requirement directly from the Fairboard and will be strictly adhered to. If you bring your own equipment to work on or load cars, you are accepting full liability of ANY and ALL incidents and occurrences that may arise from that action in any way. Period.

2. All classes will be run as single heat/feature events (one shot deals) down to the car making the last aggressive contact.

3. Drivers are responsible for the actions of their crew members. Any driver or pit person found under the influence of alcohol, drugs or becomes unruly will be disqualified and removed from the grounds. They could be barred from future events.

4. No profanity will be allowed on any portion of the car. Please remember, THIS IS A FAMILY EVENT.!!!

5. Officials have the FINAL say. It is impossible to list everything that you can and cannot do. We realize that rules will be bent, stretched, pushed to the max and tested with new ideas. Whether any stipulations or variations to these rules are allowed or not is the Officials decision, AND IT IS FINAL!! Any questions, please call first. If it doesn't say you can do it, then don't do it. Cars must be OEM stock unless otherwise noted. No painting of the frames. If the car is black it must have a 12" x 12" roof sign.

General:

1. RWD Cars no more than 106" wheelbase & FWD Cars no more than 109" wheelbase. No full frame cars.

2. All glass, plastic, and interior must be removed before arriving to the event.

3. A minimum 12" x 12" Roof Sign is Mandatory.

4. Helmet, Seat Belt, Long Sleeves/Pants & Eye Protection must be worn at all times on the track.

Body:

1. Doors may be welded all the way around on outside of body only with ¼" x 3" wide strapping no excessive overlapping of strapping is permitted.

2. Deck lids and tailgates may be welded with a 5" on 5" off rule using ¼" x 3" wide pieces of steel or 9 wired or banded in 8 spots. Deck lids and tailgates must be in original location. Deck lids may be folded down in the trunk, and may also be dipped along with speaker deck. Speaker deck can be removed, but trunk lid can only be welded to quarter panels and taillight assembly only. Nothing may be welded inside of trunk. Deck lids must be factory for make and model of car.

3. Hoods may be 9 wired in 8 places or bolted in 6 places. Bolts may be 5/8" in dia. Max. Front 2 body mounts may extend through core support and be used as front 2 of the 6 hood bolts, 1" all thread max and you cannot sleeve the all thread with anything from bottom of core support and above. A 12" hole minimum must be in the hood.

4. No interior body seam welding will be permitted. Doors can be welded on outside of body only. On preran cars the doors may be repaired back to stock. Rust repair is limited to floorboards and roofs only.

5. you may have a window bar or wire in windshield and rear window. If using metal, it can be no thicker than 3/8" and no wider than 3". You may also use 2 x 2 pipe. Not solid. These may not touch the rollover bar in any way. They can be welded to roof and firewall no more than 6" from the window area. And welded to the floor directly above rear axle. The rear window bar cannot be attached to anything else except for roof of car and floor pan, and welded 6" at the rear window on roof and 6" on floor pan.

6. Hoods must be open for inspection. Must have a 12" x 12" hole over carburetor.

7. Cars may not be smashed flat. If cars are tucked the rear quarter panels must stay at the factory height. Deck lids must be in factory location (above rain channels).

8. You can add a piece of angle (4" x 4" x ¼" max.) to top of the core support but it can be no longer than 1" wider than the radiator. No other metal permitted on core support. No other metal permitted to be welded to core support.

9. Original gas tank must be removed and replaced with a boat-type tank or fuel cell. Moved inside of car, behind driver's seat, but no further back than rear axle. No stock fuel tanks permitted inside of car.

10. Batteries must be moved to passenger side floor board and securely fastened and covered.

CAGE

1. You may have a 4-point cage surrounding the drivers compartment with a roll over bar. Bars 6" diam. Max. Must be sheet metal to sheet metal only. Dash bar must be 5" away from all sheet metal, the bar behind the seat can sit no further back than 12" from rear of driver's seat and must be at least 5" off the floor measured from the highest part of the floor/ driveshaft tunnel. You may use a rollover bar from front side of roll bar across the roof down to dash bar this may not connect to sheet metal. Door bars may be no farther forward than the firewall and extend into rear doors. On 4 door cars they must stop 2" from back of door, on 2 door cars they must stop 3" from rear wheel well on the body. The rear of these bars must be free floating and may not attach to body.
2. No angling of roll over bars permitted.
3. You may have gussets in cage at the corners. They must be within 6" of corners of bars only no other gussets will be permitted.
4. You may use 2 down legs to the frame from the rear bar down to frame these must run straight down no angling of the down legs permitted.
5. You may use a floating gas tank protector that comes off the back bar but it cannot be wider than 24". The gas tank protector or holder may go all the way back to the sheet metal. The gas tank protector must stop at the sheet metal in front of rear axle and where the rear seat meet.
6. A center bar from rear seat bar to dash bar is permitted.

#### FRAME

1. Trailer hitches and braces must be removed. No plating, pinning, heat treating, or stuffing the frame of any kind. Do not paint frame! No welds on frame or K member may exceed a single pass, no weave passes or building the weld up will be permitted.
2. No frame creasing or hammering permitted. You can notch or crease rear frame, this is to help rear of car roll not to strengthen the frame. Frame welding is limited to front and rear bumper areas. You may do one of the following not both. 1 you can weld 1 seam per side on body from firewall forward or 1 seam per side on k member with no metal added. Front frame may be shortened to front side of core support. Core support must remain in stock location.
3. If a frame section needs to be replaced or repaired (rust) you must call first. On pre-ran cars if the frame is shortened in the rear and bumper replaced the bumper shocks may not be located closer than 6" from hump plate. 6 - 1/4" x 4" x 4" fix it plates allowed. Must remain that size or smaller. 3 per side. No bending of the plate past a 90°. Plates can not overlap, must be 1" gap between them.
4. Angles for cross member can't be longer than 5" and must be within 12" from factory location.
5. For coil sprung cars you may use a hump plate. They may be 1/4" x 6" x 16" centered in the hump. They will be measured from the top center of the hump and must start no lower than the center of the frame. Hump plate must be at least 2" from rear end housing. On leaf spring cars you may use a 1/4" x 6" x 10" hump plate to be measured the same way. These hump plates may contour the frame or run straight across.
6. You may clip pre-ran cars with a single butt weld with no metal added. Must use same make and model of frame. All factory holes in frame must remain open, no welding of these holes shut are

permitted. To clip a car, you must call to get approval. Hump plate must remain a flat plate, no bending of this plate over the top or bottom of frame.

7. Front mounting points on K members may be welded to body of car. No more than a 3" welded area per side permitted. They may be bolted solid.

8. Sway bar and bracket may be welded to the frame. This must be in stock location and must only be welded to bottom of frame.

## BUMPERS

1. Homemade bumpers are permitted. They must be no bigger than 8½ "at any point. No sharp or excessive points will be permitted. This will be measured. Bumpers larger will not run, no exceptions. There will NOT be a tolerance for the 8-1/2" measurement. If using a factory bumper it may be loaded or stuffed full.

2. Bumpers may be no lower than 14" and no higher than 20" to bottom of bumper. This will be strictly enforced. Bumper seams may be welded, metal may be added to bumper, but this must be done on the inside of the bumper front bumper only. Rear bumper may be seam welded but no metal may be added to the rear bumper.

3. Bumper shocks and bumper brackets may be welded to the frame. Bumper brackets and or shocks must be no longer than 12" in length and welded to inside or outside of frame. If welded to outside of frame, they must be on the side towards the outside of car. They will be measured from back side of bumper back. You can hard nose the front bumper. You may use a 2" x 6" x ¼" plate to weld bumper to the frame, 2 per mounting point. These plates must be on side of frame, they are NOT permitted on top or bottom of frame. You may weld shock to frame. Factory bumper shocks can only be 12" from end of frame and may not be moved back on frame.

## ENGINE / TRANSMISSION

1. No chains on engine permitted. Solid or aftermarket mounts are ok.

2. 4 & 6 Cyl. Engines only. Distributor protectors are allowed, nothing that attaches to engine can be wider than the stacks i.e. dist. protector, engine cradles etc. nor can it be used to strengthen the car.

3. Oil pan and transmission pan may be plated. The plate used may be only 1" wider than the pan they are welded to. They may not connect in any way.

4. No steel bell housings allowed. You may use a transmission brace but they may not strengthen the car in any way.

## SUSPENSION

1. You may modify tie rods. A-arms must remain in stock configuration. Any tire permitted. Valve stem protectors are permitted. Rear trailing arms may be home made, but can be no bigger than 2 x 2 square tubing or pipe.
2. Upper a-arms may be welded down with a ¼" x 2" x 2" piece of steel on front and back side of upper a-arm and you may plug weld the center of the upper a-arm. Lower a-arms may not be welded. Cars do not have to bounce. Solid suspension is allowed. Coil springs in rear may be welded, wired, or chained to rear end.
3. Rear end protectors may be used but may not be used to strengthen car in any way. Leaf spring cars may replace broken springs with factory ¼ "leaf springs only. No more than 5 springs allowed per side and must have a 2" stagger. They must be mounted in factory location. You cannot change a coil spring car to a leaf spring set up.
4. Idler arm must be O.E.M. style, and mounted as from factory to frame. No bolts will be permitted all the way through the frame. Sway bar may be welded to bottom of frame in the factory location. You may use a 1 ½ " x 4" bracket or a 2" square tubing or pipe to weld to sway bar to attach to frame. You cannot move the sway bar they, must mount in factory location.
5. On front wheel drive cars, you may reinforce the rear axle assembly with 2" x 2" square tubing, 2" angle or 2" wide flat plate. This may not in any way reinforce the body of the car. Nothing bigger than 2"X 2" may be used. The 2" X 2" can attach to rear hubs.

JUDGES DECISIONS ARE FINAL!!

Rules questions Contacts

Earl Kidwell 419-618-7339

Willard Flack 614-406-1098